

4. LED Brightness Adjustment: Turn the LEDs ON. The imager head is equipped with four white LEDs to aid in inspection. Use the + and – buttons to turn ON and adjust the brightness of the LEDs.
5. Inspection: Insert the imager head and cable into the space to be inspected. Do not use the imager head or cable for anything other than an inspection device. Do not use the imager head and cable to clear a path. Do not force the imager head and cable through tight bends or spaces. These uses can damage the unit and the area to be inspected.
6. Image Rotation: If needed, the image seen on the screen can be rotated in 180-degree increments by pressing the rotate image button.
7. Power Off: When the inspection is complete, carefully withdraw the imager and cable from the inspection area. Press and hold the power button for 1 second to turn the unit OFF. The unit will automatically turn OFF 30 minutes after the last button press or if the batteries drop too low.

Viewing The microCA-25 Inspection Camera can be connected to a television or other monitor for remote viewing or recording through the included RCA cable. Open the rubber cover on the side of the screen and insert the RCA cable into the TV-OUT jack.

Insert the other end into the Video In jack on the television or monitor. The television or monitor may need to be set to the proper input to allow viewing. Figure 8–TV-OUT Jack

microCA-25 Inspection Camera

8 Cleaning **WARNING** Remove batteries before cleaning.

- Always clean the imager head and cable after use with mild soap or mild detergent.
- Gently clean the LCD with a clean dry cloth. Avoid rubbing too hard on the LCD.
- Wipe the handheld display unit down with a clean, dry cloth.

Storage The RIDGID microCA-25 Inspection Camera must be stored in a dry secure area between

-4°F(-20°C)and140°F(60°C). Storethetoolinalockedareaoutofthe eachofchildren andpeopleunfamiliarwith themicroCA-25InspectionCamera.

Removethebatteriesbeforeanylongperiod ofstorageorshippingtoavoidbattery leakage.

#### Service and Repair WARNING

Improper service or repair can make the RIDGID micro CA-25 Inspection Camera unsafe to operate. RIDGIDtoolsarewarrantedtobefreeofde-

fectsinworkmanshipandmaterial.Should thisproductrequireservice:

- ContactRIDGIDTechnicalServicesDepartmentatrtctechservices@emerson.com,orin theU.S.andCanadacall(800)519-3456

- Visitw